



Kariba™ USA



Kariba - Nomad 4.1L - General Information

Stainless Steel body



In shower mode powered by LPG / Propane Gas

Nomad in Cooker Mode - Powered by Butane/Propane Mix Gas

Description:

Nomad is the most versatile “all in one” camping gas appliance in the World claimed to be the smallest hot camp shower / cooker combination available. This compact and light weight appliance features a micro fine flame controller to adjust the shower water temperature to a desirable level. Nomad can raise ambient water temperature by some 18C (65F), delivering a warm shower to rise from 10C (50F) to some 28C (82F) for example. By simply removing the upper body housing which houses the hot coils heat exchanger including some minor adjustments, the Nomad becomes a powerful cooker capable of boiling a liter of water in less than four minutes. A quality Italian “Piezo” flame ignition is fitted including a German engineered submersible pump is supplied as standard. This appliance is designed for small families or limited groups of people who have vehicle space/weight limitations. Nomad will be appreciated by campers, hikers and adventurers for its compact and light weight design and which incorporates “dual gas” options. Carry it, hang it in a tree or from a roof rack of a car, or place it on a table for use anywhere, any time.

Frequently asked questions & answers:

- | | | | |
|--|---|--|--|
| | Does it feature an automatic shut off system? | | No. Explorer has manual control for reliability. |
| | Must water be flowing through the system? | | Yes, when the gas burner is ignited. |
| | Can this model be connected to a tap? | | Yes, only if regulated to 2.0L (0.5Gal.) flow. |
| | Can it be used by large groups showering? | | Yes, <u>but it requires to cool off in-between use.</u> |
| | Guarantee period? (RSA & North America Only) | | Six months as from date of purchase. |

Specifications: All measurements are approximate

For outdoor use only

STAINLESS STEEL BODY SIZE	: 210L x 150W x 150H mm. (8.25”L x 5.9”W x 6”H) Excludes Gas Cylinder/Canister
APPLIANCE WEIGHT UNPACKED	: 2 Kg. – (4.4 Lb.) Complete appliance.
PACKED WEIGHT	: 3.5 Kg. – (7.35 Lb.) Includes 20L (5 Gal.) Container, pump shower kit & Instructions.
HEAT EXCHANGER	: Galvanised chassis copper fins and copper coils including flame resistant hose.
4.1L 12V DC TURBO PUMP SHOWER KIT	: 12V DC 4.1L quality submersible pump - Supplied as standard equipment.
PUSH BUTTON FLAME IGNITION	: Italian “Piezo” push button electronic generator and spark plug.
RAISES WATER TEMPERATURE	: 3.8 Lt. (0.9 Gal.) p/m water flow – raises ambient water temperature by 18C (65 F).
HOT WATER Generated – From Pump	: 3.8 Lt. (0.9 Gal.) p/m water flow – rose from 10C (50F) to a maximum of 28C (82F).
CONTAINER SUPPLIED – 25L Storage Box	: 440Lx240Wx200Hmm (17.3”L x 9.5”W x 7.9”H) - Tool Box. Also used as a water well.
LP GAS CONSUMPTION	: 240/270 Grams (0.53Lb./0.59 Lb.) p/hr. (Max at 2.5L (0.6 Gal.) p/min. water flow).
WATER CONNECTIONS	: International standard garden hose type couplers.

IMPORTANT: All LP Gas specification above are rated in accordance with SANS 1539 RSA Gas bottle/cylinder vapour pressures.



Shower Hanger Solutions

SHOWER HEAD – TREE HOOK



SUCTION CUP HANGER & FLOW RESTRICTOR



4.1L Turbo Pump – Fits into a Water Jerry Can

